



GENERAL:
 ALL DIMENSIONS IN MILLIMETERS
 +/- 10mm TOLERANCES ON ALL DIMENSIONS

CONCRETE:
 STANDARD
 STANDARD ACC (ACCELERATED STRIPPING)
 10 MPa @ STRIPPING STRENGTH
 35 MPa @ 28 DAYS
 C-1 EXPOSURE CLASS
 SULPHATE RESISTANT
 6.2 CUBIC YARDS (TANK)

REINFORCING:
 ALL REINF. HAS MIN. 25mm OF COVER
 TANK:
 10M @ 300mm O/C EW
 LID:
 10M @ 300mm O/C EW
 CORNER BARS AROUND RISERS

WEIGHT:
 LID APPROX. - 9140 LBS/4155 KG
 TANK APPROX. - 19,589 LBS/8904 KG
 ASSEMBLED APPROX. - 28,729 LBS/13,059 KG

NOTES:
 DIVIDER WALL IS MONOLITHIC CAST
 JOINT SEALANT IS MASTIC SEALANT (CONCEAL CS-102)
 (NSF APPROVED SEALANT AVAILABLE FOR PORTABLE
 WATER HOLDING TANKS)
 TANK ASSEMBLED IN FACTORY
 1.5M MAXIMUM BURIAL
 INLETS ARE 4\"/>



PRODUCT:
2755 GAL / 12,499 L SEPTIC TANK

PRODUCT ID:
STC 2755

CONTRACTOR:

SCALE:
 N.T.S

REV	DATE	INI.	DESCRIPTION
0	03/23/ 20	LP	ORIGINAL DRAWING